





Conference table series



	RS075V	DS073	WS075	STag75
Dimensions External(mm)	179.5 * 123.3 * 88.3	179.5*130.7*25.2	179.5 * 123.3 * 88.3	180* 100 *143
Active Screen Area(mm)	159.6 * 95.7	159.6*95.7	163 * 97.6	162.6 * 97.3
Screen Size	7.3 inches (Dual-screen)	7.3 inches	7.5 inches (Dual-screen)	7.5 inches (Dual-screen)
Resolution(px)	800 * 480	800 * 480	800 * 480	800 * 480
Pixel Density(dpi)	127	127	124	124
Weight	380g	190g	373g	312.6g
Display Colour	Black/White/Red/Yellow/Blue/Green		Black/White/Red	
Battery Capacity	1450mAh			2600mAh
Battery Lifetime	Lasts for 8 months with one charge (5 updates / day)			5 Years (5 updates/day)
Operating Temperature	15°C~35°C		0°C~40°C	0°C~50°C



RS Series



	RS075	RS133	RS253	RS315
Dimensions External(mm)	182.5 * 128.9 * 17.1	304 * 233* 10.3	/	/
Active Screen Area(mm)	159.6 * 95.6	268.8 * 201.2	560 * 315	696.3 * 391.6
Screen Size	7.3 inches	13.3 inches	25.3 inches	31.5 inches
Resolution(px)	800 * 480	1600 * 1200	3200 * 1800	2560 * 1440
Pixel Density(dpi)	127	150	/	/
Weight	316g	760g	About 4500g	About 4650g
Display Colour	Black/White/Red/Yellow/Blue/Green			
Battery Capacity	6000mAh	4000mAh	/	/
Battery Lifetime	5 years (5 updates / day)	1 year (3 updates / day)	/	/
Operating Temperature	15°C~35°C	0°C~50°C	/	/




DS Series




	DS021/ DS021Q	DS026	DS026F	DS029/ DS029Q	DS035/ DS035Q	DS035B	DS042/ DS042Q	DS042F/ DS042B	DS116
Dimensions External(mm)	70.9 * 34.6 * 9.4	84.6 * 41 * 7.8	84.6 * 40.9 * 7.8	91.5 * 41 * 9.8	99.5 * 49.5 * 9.8	99.5 * 49.5 * 9.8	98 * 88 * 9.9	98 * 88 * 9.9	263.8 * 193.8 * 8.2
Active Screen Area(mm)	48.1 * 23.2	60.1*30.7	60.1*30.7	66.6 * 28.8	79.4 * 37.9	79.7 * 38.2	84 * 62.8	84.8 * 63.6	243.9 * 162.4
Screen Size	2.13 inches	2.66 inches	2.66 inches	2.9 inches	3.5 inches	3.5 inches	4.2 inches	4.2 inches	11.6 inches
Resolution(px)	250 * 122	296 * 152	296 * 152	296 * 128	384 * 184	384 * 184	400 * 300	400 * 300	960 * 640
Pixel Density(dpi)	130	125	125	112	122	122	119	119	100
Weight	24.5g	30g	30g	35.6g	45g	45g	85.5g	85.5g	495g
Display Colour	BWR/ BWRY	BWR	BW	BWR/ BWRY	BWR/ BWRY	BW	BWR/ BWRY	BW	BWR
Battery Capacity	1030mAh			1200mAh			2400mAh		3200mAh
Battery Lifetime	5 Years (5 updates/day)								
Operating Temperature	0 °C~ 40 °C		-25°C~25°C	0 °C~ 40 °C		-15°C~65°C	0 °C~ 40 °C	-25°C~25°C/ -15°C~65°C	0 °C~ 40 °C
Water Features	/	IP67	IP67	IP65	IP65	IP65	IP67	IP67	/




S Tag Series



产品型号	STag21F	STag21	STag26	STag29	STag29A	STag29AB	STag42	STag58	STag116	
Dimensions External(mm)	71.5 * 38.5 * 15.2	72.8 * 35.8 * 13.7	86.9 * 42.9 * 12.9	94 * 43.2 * 11.8	103.5*43.2*12.6		104.9 * 93.9 * 13.7	139.9 * 119.5 * 14.3	271.8 * 196.2 * 14.2	
Active Screen Area(mm)	48.6 * 23.7	48.6 * 23.7	60.1 * 30.7	66.9 * 29.1			84.8 * 63.6	118.8 * 88.3	244.5 * 163	
Screen Size	2.13 inches		2.66 inches	2.9 inches			4.2 inches	5.83 inches	11.6 inches	
Resolution(px)	250*122	250*122	296 * 152	296*128			400 * 300	648 * 480	960 * 640	
Pixel Density(dpi)	130	130	125	112			120	138	100	
Weight	35g	31g	38g	38g	41.7g	41.7g	92g	146g	416g	
Display Colour	BW	BWR					BW	BWR		
Battery Capacity	1500mAh	1200mAh					2400mAh	2400mAh	5500mAh	
Battery Lifetime	5 Years (5 updates/day)									
Operating Temperature	-25 ~ 25 °C	0 °C~ 40 °C					-15°C~65°C	0 °C~ 40 °C		



MTag Series



	MTag15	MTag21	MTag29	MTag29B	MTag42	MTag58	MTag75
Dimensions External(mm)	36 * 46 * 14.2	68 * 35 * 14.2	91 * 41 * 14.2	91 * 41 * 14.2	99 * 93.5 * 13.5	135.8 * 117.5 * 16.3	182.5 * 128.9 * 16.3
Active Screen Area(mm)	27 * 27	48.6 * 23.7	66.9 * 29.1	66.9 * 29.1	84.8 * 63.6	118.8 * 88.2	163.2 * 97.9
Screen Size	1.54 inches	2.13 inches	2.9 inches	2.9 inches	4.2 inches	5.83 inches	7.5 inches
Resolution(px)	152*152	250 * 122	296*128	296*128	400 * 300	648 * 480	800 * 480
Pixel Density(dpi)	142	130	112	112	119	138	124
Weight	21g	34g	45g	45g	113.5g	192g	295g
Display Colour	BWR			BW	BWR		
Battery Capacity	600mAh	1200mAh		2400mAh		4000mAh	6000mAh
Battery Lifetime	5 Years (1 update/day)	5 Years (5 updates/day)					
Operating Temperature	0 °C~ 50 °C			-15°C~65°C		0 °C~ 50 °C	
Water Features	IP65	IP65	IP65	IP65	IP67	/	/